



08/637894

IMPROVED TOILET AND SINK DRAIN PLUNGERIDENTIFICATION OF RELATED APPLICATION

This application is a continuation-in-part of U. S. Patent Application No. 08/432,245, filed on April 27, 1995, and entitled "Improved Toilet Drain Plunger", ^{now abandoned}

BACKGROUND OF THE INVENTIONFIELD OF THE INVENTION

The present invention generally relates to water and sewage drain decloggers and more particularly to an improved type of toilet and sink drain plunger.

PRIOR ART

The usual type of plunger used for declogging sinks and toilet drains and the like comprises a vertical wooden or metal handle, to the bottom of which is secured an inverted thick deformable rubber or plastic cup. The cup is initially very difficult to compress down by the handle, requiring considerable force. It then characteristically suddenly gives way, causing a sudden surge of air to pass into the drain over which it is fixed. This frequently results in loosening of the drain

1 pipe connections and water leakage therefrom. Considerable
2 force is then needed to pull the handle up to provide suction
3 force on the drain. The seal between the bottom end of the
4 cup and the area around the sink or toilet drain hole is
5 frequently inadequate and the cup may slip about over the area,
6 reducing the suction afforded by the cup.

7
8 Toilets and sinks have various curvatures in the area
9 surrounding the drain hole, making difficult the proper
10 seating of conventional drain plungers, especially toilet drain
11 plungers such as the above-described cup plunger. The most
12 efficient toilet and sink drain plunger available is that
13 shown in U. S. Patent No. 4,745,641. But even that plunger
14 is unable to seat securely over and hold in place around
15 certain toilet drain holes, due to the curved configuration
16 of the toilet around the drain hole.

17
18 Accordingly, there is a need for an improved type of
19 toilet and sink drain plunger which can seat securely over
20 or in the toilet or sink drain hole, regardless of the
21 curvature of the area around the drain hole. Such plunger
22 should be simple, efficient, capable of being easily
23 fabricated and used and be inexpensive and durable.

[illegible]

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18
- 19
- 20
- 21
- 22
- 23
- 24
- 25
- 26
- 27
- 28

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18
- 19
- 20
- 21
- 22
- 23
- 24
- 25
- 26
- 27
- 28

1 when molded, forms a rigid handle integral with the plunger
2 bellows, while the bellows portion of the mold can have a
3 separate entry port which introduces into the mold a plastic
4 which is flexible when molded but which integrally joins
5 to the handle.

6
7 The seals are of progressively smaller diameter from top
8 to bottom of the series and are of bulbous ring configurations,
9 except that the bottommost seal has a depending portion
10 which has a short vertical cylindrical configuration. The
11 seals effect their sealing on their external surface which
12 are on the outer surface of the plunger. The seals and
13 bellows have controlled flexibility and resiliency for
14 pre-selected deformability to improve their sealing and
15 pumping efficiency.

16
17 Various other features of the improved toilet and sink
18 drain plunger of the present invention are set forth in the
19 following detailed description and accompanying drawings.

20
21
22
23
24
25
26
27
28

DRAWINGS

Figure 1 is a schematic side elevation, partly broken away, of a preferred embodiment of the improved toilet and sink drain plunger of the present invention, showing the plunger in a standing resting condition;

Figure 2 is a schematic side elevation of the plunger of Figure 1, shown with the bellows of the plunger fully collapsed, that is, compressed, such as occurs for the downward stroke when the plunger is being used for declogging a toilet or sink drain;

Figure 3 is an enlarged schematic fragmentary cross-section of the sealing portion of the plunger, illustrating the curvatures of the seals;

Figure 4 is a schematic top plan view of a plurality of toilets a, b, c, d and e, illustrating different toilet bowl openings into which the improved drain plunger of the present invention can fit; and,

Figure 5 is an enlarged, fragmentary, schematic side elevation, partly in cross-section, of the improved drain plunger of Figs 1-3, showing the plunger rings in sealing contact with the opening in a kitchen sink.

1 DETAILED DESCRIPTION

2

3 FIGURES 1-3:

4

5 Now referring more particularly to Figures 1-5 of the
6 drawings, a preferred embodiment of the improved toilet
7 and sink drain plunger of the present invention is
8 schematically depicted therein. Thus, plunger 10 is shown,
9 which comprises an elongated vertical handle 12, the upper
10 end of which is formed into an expanded knob 14 adapted to
11 comfortably rest in the palm of the hand of the plunger user.
12 Preferably, handle 12 is hollow, having a central space 16
13 therein to reduce its weight, and can, if desired, be formed
14 of ^{moldable} ~~modable~~, rigid, light weight plastic such as high density
15 polyethylene plastic or the like.

16

17 The bottom portion 18 of handle 12 may include ~~external~~
18 integral threads 20 so that handle 12 can be releasably
19 connected to the bellows 22 of plunger 10.

20 ~~Under~~
21 ^{E2} Bellows 22 is generally frusto-conical in shape, has a
22 central space 24 extending therethrough defined by a closed
23 transversely extending top 26 which preferably threadably
24 receives the bottom portion 18 of handle 12, sidewalls 28
25 integral with top 26 and depending therefrom, and a bottom
26 portion 30 integrally connected to top seal 32.

27

28

Sidewalls 28 are formed into a plurality of integral horizontally extending vertically stacked interconnected pleats 34. Pleats 34 are of progressively larger diameter and preferably progressively greater flexibility from the uppermost to the lowermost of said pleats 34, so that pleats 34 easily and smoothly compress during use of plunger 10 and efficiently nest together, as shown in Figure 2 when bellows 22 is collapsed by pushing down on handle 12, avoiding the sudden air surging characteristic of conventional toilet drain plungers. If desired, the wall thickness of the pleats 34 can vary, for example, decreasing from the uppermost pleats 34 to the lowermost pleats 34 to control their flexibility.

Bellows 22 is formed of plastic or rubber, with the pleats 34 being flexible and resilient and exhibiting elastic memory. Bellows 22 can be formed in a single molding operation from, for example, low density polyethylene plastic mixed with, for example, varying proportions of copolymer of ethylene and vinyl acetate as the means to control the relative flexibility and resiliency of the various portions of bellows 22. Thus, top 26 is relatively less flexible while pleats 34 are relatively more flexible. During the molding operation a mixture of the plastics which will form the less flexible top 26 can be introduced into the mold and then a plastic mixture which results in the more flexible pleats 34 can be introduced into the mold, so that in the

single molding operation the bellows that molded will exhibit the required differences in flexibility between top 26 and pleats 34. This is a known molding procedure.

Seal 32 is ring-shaped and relatively less flexible than plate 34 due to its size and shape and/or wall thickness and also, if required, due to a change in the composition of the plastic mixture from that of the pleats 34. Seal 32 has an annular wall 35 which curves downwardly and inwardly from its point of connection with the underside of the lowermost of pleats 34 to its point of connection with the upper end of the second seal 36 of plunger 10.

Seal 36 is also ring-shaped but relatively more bulbous and is longer than seal 32, curving continuously downwardly to its narrowest diameter at its point of connection with the lowermost third seal 38.

Seal 38 is relatively short in height and also ring-shaped in its upper portion 40, from the bottom of which vertically depends its lower portion 42, which is in the form of a short thin vertical cylindrical wall 44 with a horizontal bottom end 46 which enables plunger 10 to rest in the upright position of Figure 1. Portion 40 has a diameter slightly greater than that of the lower end of seal 36, while portion ⁴⁰~~32~~ is of smaller diameter than portion ³²~~40~~. Seals 36 and 38 are similar in flexibility and construction to seal 32,

that is, less flexible than bellows 22.

Seal 32 is of greater diameter than seal 36, while the maximum diameter of seal 36 is greater than that of seal 38. Seals 32, 36 and 38 provide their sealing effect on their external surfaces which are on the outer surface of plunger 10. With this arrangement, plunger 10 can be used to efficiently seal sink and toilet drain holes of various sizes and shapes. Seals 32, 36 and 38 can be formed in a single molding operation. Moreover, space 24 extends down through the interior of seals 32, 36 and 38. Seals 32, 36 and 38 can be formed of the same materials as bellows but of different relative proportions of those materials than for bellows 22 so as to control their flexibility. Moreover, their size, shape and wall thickness contribute to their degree of flexibility.

Wall 44 can be placed around a drain hole or within it. The edges of the drain hole can abut the underside of portion 40, seal 36 or seal 32, depending on the size of the drain hole. Seals 32, 36 and 38 are sufficiently deformable to increase their sealing effect as they are pressed against the drain hole edges during use of plunger 10. In Fig. 5, it is seen that when plunger 10 is inserted into a drain hole, in this instance, a stepped kitchen sink drain hole 50 defined by sink 52, bulbous curved seal 36 is deformed inwardly by sink ledge 54 at point 56 forming a tight seal

06637394-04259

1 within the scope of the appended claims form part of the
2 present invention.

3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28